

## Code EC45WSX – Stainless Steel Cylinder Canopy



### 3 SPEED MOTOR

This range hood provides the option of 4 different speed levels ensuring you have the option to use your range hood at a low, medium or high level of operation.

### HIGH EXTRACTION CAPACITY

The extraction capacity of 861m<sup>3</sup>/hr provides strength and power to this stylish range hood.

### QUIET NOISE LEVEL

A very quiet motor ensures the range hood has a very quiet noise level.

**Decibel Rating: 57-65 DBa**

### FUNCTIONS

- Soft Touch control Rangehood
- Modern European Design
- Twin Down lights 20W
- Strong Extraction capacity: 861m<sup>3</sup>/h
- 10 amp Connection
- 3 Speed Levels
- Decibel rating: 57-65 (4<sup>th</sup> speed) decibels
- Flue Diameter 150mm

### TIPS FOR BETTER USE

- Leave your range hood on for 15 minutes after the cooking of the food to remove all odors, steam etc.
  - The dishwasher-safe cassette filters need to be cleaned after approximately 2 months of standard operation
  - It is recommended the range hood be installed between 650mm and 750mm above the cook top
  - It is also recommended that fumes from the range hood be ducted out into the atmosphere.
  - Turn off the range hood before attempting to clean
- Installation must be through qualified technician.**

### ELECTRICAL REQUIREMENT:

Range hood is supplied with 10amp cord & plug.

### OPTIONAL ACCESSORIES

#### RECIRCULATING ACCESSORIES

Carbon Filter Code: ACK98498 (requires x2)

#### RANGEHOOD VENTILATION KITS

RHKE65 – Wall – Eave vent kit

RHKMR65 – Universal metal roof kit, includes flashing

RHKTR65 – Universal tile roof kit, includes flashing

### PRODUCT DIMENSIONS

