Beuro appliances

Code EVR60FVSS - 60cm Front Vent Recirculating Rangehood



DISHWASHER SAFE CASETTE FILTERS

The cassette filters can be placed in a dishwasher for easy cleaning and can easily be removed & re-connected from the range hood.



DUCTED OR RECIRCULATING OPTIONS

This rangehood can be vented as standard or has the option of recirculated venting, with its front vented capabilities. If installing as a recirculating rangehood, you must use the 80mm front fascia which is supplied as standard.

HIGH EXTRACTION CAPACITY

The extraction capacity of 400m³/hr provides strength and power to this stylish range hood.

QUIET NOISE LEVEL

A very quiet motor ensures the range hood has a very quiet noise level.

FEATURES

- Ducted or recirculating options
- Stainless steel front fascia with two panel size options
 - Standard panel size: 40mm (separate in box)
 - Wider panel size: 80mm (fitted on unit)
- · Twin motors
- 400m3 / hr extraction capacity
- · Dual incandescent lights
- · Aluminum grease filter
- •120mm flue diameter
- · Decibel rating: 47-69dBA
- Carbon filters supplied with unit (Model No. CFM60FVSS)







Recirculating vents

Carbon Filter on motors

Control Panel switch

TIPS FOR BETTER USE

- Leave your range hood on for 15 minutes after the cooking of the food to remove all odors, steam etc.
- The dishwasher-safe cassette filters need to be cleaned after approximately 2 months of standard operation
- It is recommended the range hood be installed between 650mm and 750mm above the cook top
- Turn off the range hood before attempting to clean
- -Installation must be through qualified technician.

PRODUCT DIMENSIONS

ELECTRICAL REQUIREMENT:

Range hood is supplied with 10amp cord & plug.

DECIBEL RATING

47-69 dBA

WEIGHT:

9.0kg (net) / 10.2 kg (gross)

RECIRCULATING ACCESSORIES (OPTIONAL)

Product Code: CFM60FVSS Carbon filter (Requires x2)

RANGEHOOD VENTILATION KITS (OPTIONAL)

RHKE65 - Wall - Eave vent kit

RHKMR65 – Universal metal roof kit, includes flashing

RHKTR65 - Universal tile roof kit, includes flashing

FILTER CLEANING INFORMATION:

Cassette mesh filter: requires cleaning monthly. This will ensure no interruptions with airflow operation.

527 Ø120 175 40 280 308-443